

Ampure Go™

Portable Electric Vehicle Cordset



Key Features

- Dual voltage (120V & 240V) cordset
- State-of-the-art safety features
- Compact, portable, 32amps @240V
- 3 LED status bar
- IP67 Rated IC-CPD can be submerged up to 3ft
- UL and cUL certified
- NEMA enclosure
- IEC grid plug to charge in any environment
- Easy to use, simply plug-in and charge
- J1772 Coupler type which is applicable for all vehicles meeting US standards
- Easily mount in your garage or on a wall with the included bracket

Technical Specifications

| | |
|-----------------------|---|
| Max Current | 240V @ 32A (7.7kW); 120V @ 12A (1.4kW) |
| System Package | 320 x 320 x 100 mm |
| AC Compatibility | 85 - 265 VAC, 45 - 65 Hz |
| Plug Type | NEMA 14-50 & NEMA 5-15 |
| Cable Length | 20 ft (6m) |
| Weight | 9 lbs (4.1 kg) - module |
| Operating Temperature | -30°C (-22°F) to +50°C (122°F) |
| Ingress Protection | Yes NEMA 6P watertight, IP67 (up to 3ft submerged) IC-CPD is IP67 |
| Certified Altitude | 13,123 ft (4000m) |
| Vehicle Connector | J1772 |
| Certification | UL, cUL |
| HMI | 3 LED Status Bar |

